



BIOSAN

Bactericidal neutral detergent for any kind of surface

APPLICATIONS

BIOSAN is a neutral detergent for cleaning and maintenance of all hard and resilient surfaces such as: granite, marble, slate, natural stones, treated terracotta, porcelain stoneware, linoleum, clinker, ceramics, parquet floorings, synthetic materials, sanitary fittings, etc.

The products can be used everywhere, from door jambs and frames to floors and walls, washable plasticized wall-papers, ceramic tiles, imitation leather armchairs, motor-car interiors and plastic coatings.

Thanks to its very special countless applications and to its antibacterial power, **BIOSAN** is largely demanded since many years, not only for household applications, but it is more and more frequently being applied in hospitals, hotels, industries and the like.

BIOSAN is a neutral product with pH7, containing a pleasant menthol-pine fragrance.

HOW TO USE

Dilution: the dilution ratios change according to the type of dirt to be removed.

Application: to treat treated terracotta and all washable surfaces, apply BIOSAN diluting 20-30 grams of product into 10 liters of water. Dip the cloth in the solution and clean the surfaces, then rinse.

To remove marks left by rubber shoes on terracotta floors, use BIOSAN undiluted on a wet cloth and rub softly on the black marks to be removed (there is no need to rub in too much).

Black marks or stripes can be easily removed without spoiling the treatment.

BIOSAN is very suitable for being applied using “wash-and-dry” machines.

WARNINGS

The MSDS is available upon request.

PACKAGING

Bottle of 1 kg. Box of 12/24 pcs
Drum of 5 kg. Box of 6 pcs

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0 and 30°C and shielded from direct sunlight. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the

products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE